

Hot-Melt Applicator TR 55 LCD



Subject to modifications

Fig. TR 55 LCD

Made in Germany

The glue gun TR 55 LCD works with hot-melt glues of high and low viscosities in granulate and stick forms.

The hot-melt adhesive is extruded through air pressure. Pneumatic glue guns increase work speed and simplify exact dosing of the glue. Thanks to the built in electronic temperature regulation the glue gun is ready to work within 3 to 10 minutes. Furthermore, it keeps the temperature on a constant level thus is a perfect suit for processing temperature-sensitive hot-melt glue. A LCD-display and push-buttons allow a precise temperature adjustment. This way, the user always knows the current temperature of the glue applicator and is able to apply the glue at the intended

temperature.

The glue gun TR 55 LCD can be loaded with granulate, pillows and 43 mm slugs. It offers maximum flexibility for choosing the right glue and lets you benefit from cost-advantages of different shapes of hot-melt.

The notably large capacity of 330 ml allows continuous work for a long time.

The number of possible application patterns is widely extended by the Reka nozzle range. Almost all of the offered nozzles can be used with every Reka glue gun in combination with a separate adapter.

Technical Data

	TR 55 LCD	TR 55 LCD	TR 55 LCD HT	TR 55 LCD HT
Article Number	5424 (230 V)	5427 (120 V)	5384 (230 V)	5388 (120 V)
Weight	1400 g			
Power Supply	230 V / 50 Hz	120 V / 60 Hz	230 V / 50 Hz	120 V / 60 Hz
Power Consumption	600 Watt	400 Watt	600 Watt	400 Watt
Current Consumption	2,6 A	3,3 A	2,6 A	3,3 A
Degree of protection	IP 30			
Class of protection	I			
Temperature control	Electronic			
Temperature limitation	Temperature monitor			
Temperature indication	digital			
Operating temperature	50 – 210 °C	50 – 210 °C	50 – 235 °C	50 – 235 °C
			(250°C on request)	(250°C on request)
Consistency of temperature	± 2 °C			
Heat-up time	approx. 3 – 10 min.			
Gross Tank Capacity	330 ml			
Conveying system	Air pressure			
Operating pressure	0,5 – 6 bar			
Length of electric cord	8,5 m			
Length of air tube	5 m			
Length of connection kit	3 m			
Recommended melts	Hot-melt granulate, pillows and 43mm sticks/slugs			

Accessories

- 1 # 3518 Footswitch
- 2 # 3746 Stationary equipment
- 3 # 5563 Premelter
- 4 # 2770 Stand for storing
- 5 # 3544 Balancer
- 6 # 3519 Cleaning Liquid Meltanova
- 7 # 3465 Nozzle Set M14 Professional
- 8 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
 Siemensstr. 6
 DE-76344 Eggenstein
 Telefon: +49 721 970 780
 Telefax: +49 721 705 069
 E-Mail: in-fo@reka-klebetechnik.de
 Internet: www.reka-klebetechnik.de