

Hot-Melt Applicator MS 200.E



Fig. MS 200.E

Made in Germany

Subject to modifications

Hot-Melt Glue Applicator Gun MS 200.E – Easy Processing of Hot-Melt without compressed air.

The MS 200.E lets you process hot-melt granulates, pillows and even 43mm sticks effortlessly and hassle-free. It doesn't even require air pressure and thanks to the 500 watt heater it is ready to go within minutes. The comfort locking and big opening lets you fill the 250 ml tank with ease.

Thanks to the electronic temperature regulation the hot glue is kept at a precise temperature and protected against coking. This makes the MS 200.E a great tool for temperature sensitive hot-melts like PA, polyamide based glues. The adjustable temperature range is 30 to 200 degrees celsius, this enables you to apply materials with an especially low melting point like wax.

The MS 200.E is well suited to work in dusty and demanding work environments. The ergonomic handle and adjustable trigger enable a continuous workflow and is well-suited for smaller hands as well as right and left-handed people alike.

The integrated magnetic foot lets you pick the applicator up and put it down in the blink of an eye and is a real time saver. A wire stand makes sure the device can also be placed securely on non-magnetic surfaces.

Combined with the reka nozzle portfolio the MS 200.E handles countless applications comfortably, powerful and professional.

Technical Data

	<i>MS 200.E</i>	
<i>Article Number</i>	<i>5602 (230 V)</i>	<i>5603 (120 V)</i>
<i>Weight</i>	<i>1220 g</i>	
<i>Power Supply</i>	<i>230 V / 50 Hz</i>	<i>120 V / 60 Hz</i>
<i>Power Consumption</i>	<i>500 Watt</i>	
<i>Current Consumption</i>	<i>2,2 A</i>	<i>4,2 A</i>
<i>Degree of protection</i>	<i>IP 30</i>	
<i>Class of protection</i>	<i>I</i>	
<i>Temperature control</i>	<i>Electronic</i>	
<i>Temperature limitation</i>	<i>Temperature monitor</i>	
<i>Operating temperature</i>	<i>30 – 200 °C</i>	
<i>Consistency of temperature</i>	<i>± 2 °C</i>	
<i>Heat-up time</i>	<i>approx. 5 min.</i>	
<i>Gross Tank Capacity</i>	<i>250 ml</i>	
<i>Conveying system</i>	<i>Mechanics</i>	
<i>Length of electric cord</i>	<i>2,5 m</i>	
<i>Recommended melts</i>	<i>Hot-melt granulate, pillows and 43mm sticks/slugs</i>	

Accessories

- 1 # 5563 Premelter
- 2 # 3519 Cleaning Liquid Meltanova
- 3 # 3544 Balancer
- 4 # 2100 Stand for Storing
- 5 # 3465 Nozzle Set M14 Professional
- 6 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de