

Technical Data

	<i>MS 200.LCD</i>	
<i>Article Number</i>	<i>5609 (230 V)</i>	<i>5611 (120 V)</i>
<i>Weight</i>	<i>1220 g</i>	
<i>Power Supply</i>	<i>230 V / 50 Hz</i>	<i>120 V / 60 Hz</i>
<i>Power Consumption</i>	<i>500 Watt</i>	
<i>Current Consumption</i>	<i>2,6 A</i>	<i>4,2 A</i>
<i>Degree of protection</i>	<i>IP 30</i>	
<i>Class of protection</i>	<i>I</i>	
<i>Temperature control</i>	<i>Electronic</i>	
<i>Temperature limitation</i>	<i>Temperature monitor</i>	
<i>Operating temperature</i>	<i>30 – 205 °C</i>	<i>85 - 405 °F</i>
<i>Consistency of temperature</i>	<i>± 2 °C</i>	
<i>Heat-up time</i>	<i>approx. 5 min.</i>	
<i>Gross Tank Capacity</i>	<i>250 ml</i>	
<i>Conveying system</i>	<i>Mechanics</i>	
<i>Length of electric cord</i>	<i>3,5 m</i>	
<i>Plug Type</i>	<i>E+F</i>	<i>B other upon request</i>
<i>Recommended melts</i>	<i>Hot-melt granulate, pillows and 43mm sticks/slugs</i>	
<i>Standard Nozzle</i>	<i>2,0 mm # 12496</i>	

Accessories

- 1 # 5563 Premelter
- 2 # 3519 Cleaning Liquid Meltanova
- 3 # 3544 Balancer
- 4 # 2100 Stand for Storing
- 5 # 2381 Stand for Storing .2 (NEW!)
- 6 # 3465 Nozzle Set M14 Professional
- 7 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de