

Hot-Melt Applicator MS 80



Fig. MS 80

Made in Germany

Subject to modifications

The MS 80 glue gun works with granular hot-melts without compressed air.

The MS 80 and MS 200 glue guns are the only glue guns working with hot-melt granulate without compressed air. Simply connect them to the socket – ready. Use the thermostatic controls to set the requested temperature between 50 °C and 200 °C and you always work with the optimum glue temperature.

Pull the trigger to apply the melted granulate. There is a great number of accessories making the MS 80 suitable for many applications. The MS 80 gets light like a feather when it is fixed to a balancer. The MS 80 has proven successful in practice over a long period of time.

Technical Data

	<i>MS 80</i>	
<i>Article Number</i>	<i>5551 (230 V)</i>	<i>5560 (120 V)</i>
<i>Weight</i>	<i>850 g</i>	
<i>Power Supply</i>	<i>230 V / 50 Hz</i>	<i>120 V / 60 Hz</i>
<i>Power Consumption</i>	<i>200 Watt</i>	
<i>Current Consumption</i>	<i>0,9 A</i>	<i>1,7 A</i>
<i>Degree of protection</i>	<i>IP 30</i>	
<i>Class of protection</i>	<i>I</i>	
<i>Temperature control</i>	<i>Thermostat</i>	
<i>Operating temperature</i>	<i>50 – 200 °C</i>	
<i>Consistency of temperature</i>	<i>± 5 °C</i>	
<i>Heat-up time</i>	<i>approx. 10 min.</i>	
<i>Gross Tank Capacity</i>	<i>150 ml</i>	
<i>Conveying system</i>	<i>Mechanics</i>	
<i>Length of electric cord</i>	<i>2,5 m</i>	
<i>Plug Type</i>	<i>E+F</i>	<i>B other upon request</i>
<i>Recommended melts</i>	<i>Hot-melt granulate, pillows and chips</i>	
<i>Standard Nozzle</i>	<i>1,75 mm # 3911</i>	<i>1,9 mm # 1143</i>

Accessories

- 1 # 5563 Premelter
- 2 # 3519 Cleaning Liquid Meltanova
- 3 # 3544 Balancer
- 4 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de