

Hot-Melt Adhesive Spray System TR 60 LCD



Subject to modifications

Fig. TR 60 LCD

Made in Germany

The TR 60 LCD Hot-Spray-System consists of the TR 60 LCD glue gun and the stand on which the gun may be deposited.

The TR 60 LCD is a hot-melt adhesive spray system. Spray application is a non-contact glue application, which means it goes easy on the materials that are about to be glued. Also, spray application allows covering great areas and using very little glue. A stand for storing with built in pressure regulator and manometer is part of the system and permanently attached to the TR 60 LCD, so setting the right glue output and spray pattern becomes very easy. The hot-melt adhesive is extruded through air pressure. Pneumatic glue guns increase work speed and simplify exact dosing of the glue. Thanks to the built in electronic temperature regulation the glue gun is ready to work within 3 to 10 minutes. Further more, it keeps the temperature on a constant level thus is a perfect suit for processing temperature-sensitive hot-melt glue.

A LCD-display and push-buttons allow a precise temperature adjustment. This way, the user always knows the current temperature of the glue applicator and is able to apply the glue at the intended temperature.

The TR 60 LCD hot-melt glue gun can be loaded with granulate, pillows and 43 mm slugs. It offers maximum flexibility for choosing the right glue and lets you benefit from cost-advantages of different shapes of hot-melt.

The capacity of 250 ml is sufficient for numerous gluings.

The TR 60 LCD can be switched to dot- and line-application with an adapter.

The number of possible application patterns is widely extended by the Reka nozzle range. Almost all of the offered nozzles can be used with every Reka glue gun in combination with a separate adapter.

Technical Data

	TR 60 LCD	TR 60 LCD	TR 60 LCD HT	TR 60 LCD HT
Article Number	5461 (230 V)	5462 (120 V)	5382 (230 V)	120 V (request)
Weight	1200 g			
Power Supply	230 V / 50 Hz	120 V / 60 Hz	230 V / 50 Hz	
Power Consumption	480 Watt	400 Watt	480 Watt	
Current Consumption	2,09 A	3,3 A	2,09 A	
Degree of protection	IP 30			
Class of protection	I			
Temperature control	Electronic			
Temperature limitation	Temperature monitor			
Operating temperature	50 – 210 °C	50 – 210 °C	50 – 235 °C	(250°C on request)
Consistency of temperature	± 2 °C			
Temperature indication	digital			
Heat-up time	approx. 3 – 10 min.			
Gross Tank Capacity	250 ml			
Conveying system	Air pressure			
Operating pressure	0,5 – 6 bar			
Length of electric cord	4 m			
Plug Type	E+F	B		other upon request
Length of connections (stand to handgun)	4,5 m			
Length of connection kit	3 m			
Recommended melts	Hot-melt granulate, pillows and 43mm sticks/slugs			
Standard Nozzle	1,0 mm # 3051 + Cap # 3088			

Accessories

- 1 # 3518 Footswitch
- 2 # 3746 Stationary equipment
- 3 # 5563 Premelter
- 4 # 2770 Stand for storing
- 5 # 3544 Balancer
- 6 # 3522 Adapter for dots/line application
- 7 # 3466 Nozzle Set M10 Professional
- 8 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
 Siemensstr. 6
 DE-76344 Eggenstein
 Telefon: +49 721 970 780
 Telefax: +49 721 705 069
 E-Mail: in-fo@reka-klebetechnik.de
 Internet: www.reka-klebetechnik.de