

TR 700 Cartridge Gun



Fig. TR 700

Made in Germany

The TR 700 cartridge gun applies hot-melt adhesives from 310 ml aluminium cartridges in dots, beads, or other standard nozzle forms.

The TR 700 lets you apply hot-melt adhesive as dots and lines.

The hot-melt adhesive is extruded through air pressure. Pneumatic glue guns increase work speed and simplify exact dosing of the glue.

The working-temperature of the glue applicator is controlled by a thermostat and set to 120 °C.

The TR 700 glue gun uses 310 ml aluminium hot-melt glue cartridges, which for instance can contain PUR-

hot-melt glue or POR-hot-melt adhesive. The cartridges can be swapped easily and hassle-free. The optional cartridge pre-heater KVG heats up the glue before use and increases the possible glue output per hour.

The number of possible application patterns is widely extended by the Reka nozzle range. Almost all of the offered nozzles can be used with every Reka glue gun in combination with a separate adapter.

Technical Data

	<i>TR 700</i>	
<i>Article Number</i>	<i>5385 (230 V)</i>	<i>5370 (120 V)</i>
<i>Weight</i>	<i>1100 g</i>	
<i>Power Supply</i>	<i>230 V / 50 Hz</i>	<i>120 V / 60 Hz</i>
<i>Power Consumption</i>	<i>400 Watt (230 V)</i>	<i>400 Watt (120 V)</i>
<i>Current Consumption</i>	<i>1,75 A</i>	<i>3,3 A</i>
<i>Degree of protection</i>	<i>IP 30</i>	
<i>Class of protection</i>	<i>I</i>	
<i>Temperature control</i>	<i>Thermostat</i>	
<i>Temperature limitation</i>	<i>Temperature monitor</i>	
<i>Operating temperature</i>	<i>120 °C</i>	
<i>Consistency of temperature</i>	<i>± 5 °C</i>	
<i>Heat-up time</i>	<i>approx. 3 – 10 min.</i>	
<i>Gross Tank Capacity</i>	<i>310 ml</i>	
<i>Conveying system</i>	<i>Air pressure</i>	
<i>Operating pressure</i>	<i>0,5 – 6 bar</i>	
<i>Length of electric cord</i>	<i>8,5 m</i>	
<i>Plug Type</i>	<i>E+F</i>	<i>B other upon request</i>
<i>Length of air tube</i>	<i>5 m</i>	
<i>Length of connection kit</i>	<i>3 m</i>	
<i>Recommended melts</i>	<i>310 ml hot-melt cartridges</i>	
<i>Standard Nozzle</i>	<i>1,9 mm # 1143 + Adapter # 2958</i>	

Accessories

- 1 # 3518 Footswitch*
- 2 # 3746 Stationary equipment*
- 3 # 5398 Cartridge Preheater*
- 4 # 2770 Stand for storing*
- 5 # 3544 Balancer*
- 6 # 7099 Blank cartridge incl. piston*
- 7 # 3466 Nozzle Set M10 Professional*
- 8 Inquire about our nozzle range*

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de